



DECLARATION OF THE CHARACTERISTICS OF A CONSTRUCTION PRODUCT

No. 06/2026

1. Unique identification code of the product-type:

Concrete kerb units

2. Type, batch or serial number or any other element allowing identification of the construction product

Concrete and reinforced concrete products- concrete curbs with a smooth visible surface and side slope, with nominal dimensions 800/240/180 mm

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

EN 1340:2003.AC: 2006 „Concrete kerb units – Requirements and test methods

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) of Regulation (EU) No. 305/2011:

GLOBI M.I SH.P.K

**Ferizaj Highway, km 3 ,
GJILAN, KOSOVO
+383 49 944 113 : +383 49 944 114
Globi-mi.com**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

6. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Regulation (EU) 305/2011

Performed determining the type of the product based on test under:

System 3

and issued:

Test Protocol No. 316-1 -236 / 26.05.2026
From TESTING CENTER FOR CONSTRUCTION (TCC) at
BUILDING RESEARCH INSTITUTE- NISI Ltd

ACCREDITED ACCORDING TO EN ISO/IEC 17025:2018
CERTIFICATE REG. NO.88 JIH/14.06.2024
ISSUED BY EA BSA AND VALID UNTIL 07.10.2026
SECTOR CONCRETE& REINFORCING STEEL, BUILDING MATERIALS &
PRODUCTS

from Testing Laboratory Solar Project Ltd, NB 2145

7. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Water Absorption	5.7%	EN 1340:2003/AC:2006
Resistance to freeze-thaw with de-icing salts –Mass loss after freeze/thaw test	0.8 kg/m2	EN 1340:2003/AC:2006
Bending strength	4.7 MPa	EN 1340:2003/AC:2006
Abrasion resistance	18700 mm3	EN 1340:2003/AC:2006

8. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 7.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by: